



SKID STEER LOADER

4200V



KEY FEATURES

- ▲ Low Effort Joystick Controls
- ▲ Air Suspension Seat
- ▲ Cab Enclosure with Heat and Air Conditioning
- ▲ High Flow Auxiliary Hydraulics
- ▲ 2 Travel Speeds
- ▲ Power-A-Tach® Quick Coupler
- ▲ Selectable Self Level
- ▲ Load Sensing Hydraulic System

KEY SPECIFICATIONS

- ▲ Operating capacity (50%) – 1906 kg
- ▲ Overall height to top of ROPS – 2083 mm
- ▲ 90 kW @ 2200 rpm Deutz engine
- ▲ Deutz / TD 3.6 EPA Stage 4 engine*
- ▲ 480 Nm @ 1600 maximum torque
- ▲ 40.2 kn tilt breakout force
- ▲ 3653 mm – height to hinge pin
- ▲ 2057 mm overall machine width
- ▲ 5291 kg operating weight

* Region 2 - Stage 3A Engine

SKID STEER LOADER

4200V



SPECIFICATIONS

DIMENSIONS	Overall Operating Height - Fully Raised	4744 mm
	Height to Hinge Pin - Fully Raised	3653 mm
	Overall Height to Top of ROPS	2083 mm
	Overall Length with Bucket	4039 mm w/2134 mm Bucket
	Dump Angle at Full Height	31°
	Dump Height	2921 mm
	Dump Reach at Full Height	965 mm
	Rollback at Ground	30°
	Rollback Angle at Full Height	98°
	Wheelbase	1384 mm
	Overall Width - Less Bucket	2057 mm
	Bucket Width	2134 mm
	Ground Clearance to Chassis	197 mm
	Overall Length - Less Bucket	3124 mm
	Departure Angle	18°
	Clearance Circle - Front w/ Bucket	2484 mm
	Clearance Circle - Front w/o Bucket	1410 mm
Clearance Circle - Rear	1880 mm	
Standard Specification Tire Size	14.00x17.5 HD	
CAPACITY & WEIGHTS	Rated Operating Capacity	1905 kg
	UREA/DEF Tank	15L
	Fuel Tank	144L
	Travel Speed - Maximum	18.7 km/hr
	Operating Weight - Approximate	5291 kg
ENGINE	Make	Deutz
	Model	TCD 3.6 Stage 4
	Gross Power @ rpm	90 kW @ 2200 rpm
	Maximum Torque @ rpm	480 Nm @ 1600 rpm
	Displacement	3.6L
ELECTRICAL SYSTEM	Battery	12-volt 1500 CCA
	Starter (kW)	4 kW
	Alternator	12-volt 120-amp
HYDRAULICS	Auxiliary Hydraulics - Standard	114 L/min
	High-Flow Auxiliary Hydraulics - Option	155 L/min
	Reservoir Capacity (L)	60L
NOISE & VIBRATION	Noise at Driving Position (LpA)	82.9 dB(A)
	Noise to Environment (LwA)	102.5 dB(A)
	Vibration on Hands/Arms	1.155 m/s ²
	Whole Body Vibration	1.091 m/s ²

* Region 2 - Stage 3A Engine



MUSTANG MFG.

mustangmfg.com

STANDARD FEATURES

- ▲ Adjustable Arm Rests/ 14-Pin Connector Control Towers
- ▲ Air Ride Suspension Seat
- ▲ Power-A-Tach® Attachment Mounting System
- ▲ Anti-Vandalism Protection
- ▲ Back-Up Alarm
- ▲ Battery Disconnect
- ▲ Block Heater
- ▲ Cab with Heat & Air Conditioning
- ▲ Engine Auto-Shutdown System
- ▲ Engine Glow Plugs
- ▲ Foot and Hand throttles
- ▲ Front and Rear Window Wipers
- ▲ Multi-function color display screens
- ▲ High-Flow Auxiliary Hydraulics
- ▲ Horn
- ▲ Hydraglide™ Ride Control
- ▲ Hydraloc™ Safety System
- ▲ Hydrostatic Drive - Pilot
- ▲ Load Sensing Hydraulic System
- ▲ Integral Access Plate
- ▲ Joystick Controls - Pilot
- ▲ Lift Arm Support Device
- ▲ Operator Restraint Bar
- ▲ Radio with Hands-Free Bluetooth
- ▲ ROPS/FOPS Level II Overhead Guard
- ▲ Self-Leveling Lift Action
- ▲ Sound Reduction Material
- ▲ Turbo-charged engine
- ▲ Two-speed drive
- ▲ Work Lights - Front and Rear



OPTIONAL FEATURES

- ▲ Impact Resistant Door
- ▲ 76 mm Seatbelt and Shoulder Strap
- ▲ Rear View Camera
- ▲ Brake Release
- ▲ Rotating Beacon
- ▲ Easy Manager Telematics

Mustang reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Mustang reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

147 Indiana Avenue, West Bend, WI 53095 | Phone: (262) 334-9461