

# PB S225-23ES 4x4

Self-propelled Scissor lift

Working height 22.30 m / indoor + outdoor

Rough terrain 4x4 / Automatic outrigger system



Type	PB S225-23ES 4x4
Operation area	indoor+outdoor
Drive	Electro-hydraulic
Working height	22.30 m
Platform height - raised	20.30 m
Drivable at full height	Yes
Drive speed (stowed / raised)	5.4 / 0.51 km/h
Platform size (l x w)	4.50 x 2.30 m
Platform size max. (l x w)	7.20 x 2.30 m
Lift capacity	750kg
Lift capacity platform extension	750kg
Platform occupancy	4

Gross weight	14.000 kg*
Total length	4.84 m
Total width	2.30 m
Total height	3.82 m
Transport height – rails folded	2.91 m
Turning radius – outside	4.11 m
Ground clearance – center	0.39 m

Gradeability	30 %
4-wheel-drive	Yes
Differential lock	Yes
Automatic outrigger system	Yes
Permitted tilt angle	3° (0,3° supported)
Max. outrigger load	38 KN
Motor power	35kW
Battery capacity	625 Ah5, 80V



Technical data are subject to change. \*Provisional data



PB Liftechnik GmbH | Gewerbegebiet Gassenäcker | 89429 Oberbechingen / Germany

Telefon: +49 (0) 90 77 – 95 00 – 0 | Telefax: +49 (0) 90 77 – 95 00 – 40

E-Mail: [info@PBgmbh.de](mailto:info@PBgmbh.de) | Website: [www.PBgmbh.de](http://www.PBgmbh.de)

