

VTS95

Designed for maximum performance and high productivity

The new McCloskey [™] VTS95 tracked shredder features an extremely aggressive knife design and open cutting table offering a range of knives for different types of waste. The VTS95 ensures the most efficient waste handling across applications. As with all the McCloskey[™] products, the VTS95 has been designed with absolute focus on the machine operator. In addition to the highest level of quality and performance, significant benefits include simple and fast assembly times, easy maintenance and short downtime.

Features

- Aggressive 8 Knife Samurai, heavy duty cutting table
- Danfoss Electrical control unit
- Variable speed main conveyor
- 4 Meter tracks for superior maneuverability and stability
- CAT C15 403 KW (540HP) Stage V/Tier 4 Final
- Fuel efficient Hydraulics system
- User Friendly Hydraulic Controls
- Double Hydrostatic drive transmission
- Access ladder mounted at the front of the cutting table



Convevor Belt

Conveyor belt speed can be precisely adjusted to suit the particular waste being processed.

Low Loader

Low load height, allowing easier loading with a smaller loader. A mounted ladder on the cutting table ensures good access.

Tracked Machine

Tracked machine allow for easy mobility throughout site and moved during operation.



Aggressive cutting table Cutting chamber has a 10,000 hour lifetime – choose from 8 or 10 knife layout. Cutting table includes a mounted ladder to ensure good



mccloskeyinternational.com

©Copyright 2020 McCloskey International. All rights reserved. McCloskey is a trademark of McCloskey International.

access.

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate -McCloskey International assumes no liability resulting from errors or omissions in this document.

SPECIFICATION DATA

Dimensions And Capacities

Length – working (Max) Height – working (Max) Length – transport Width - transport Height - transport Over hang - transport Maximum production rate Average fuel consumption 15m (49'-2") 3.5m (11'-6") 9.43m (30'-11") 2.95m (9'-8") 3.53m (11'-7") 0.6m (1'-11") 100TPH (Material dependent) 60 L/Hour (15.5 US Gal) 35,000KG (77,160 lbs.)

Cutting Table

Machine weight

Number of shafts 2 Rotating speed Number of knives 8/10 Number of counter knives 16/20 Cutting area Knife type Chamber weight

16-41/27-56 RPM 2420mm X 2000mm (95" X 79") Samurai 14,900KG (32,850 lbs.)

Grain Size

8 knife standard 10 knife option

< 300 mm (< 12") < 200 mm (< 8")

Capacity Per Hour

lousehold waste	
Demolition wood	
ndustrial waste	
Bulk waste	

Up to 100 Ton Up to 70 Ton Up to 35 Ton Up to 50 Ton